Material Safety Data Sheet

PURITY_{TM} FG WO WHITE MINERAL OIL 15, 35, 68, 90



Product and company identification

Common name

: PURITY™ FG WO WHITE MINERAL OIL 15, 35, 68, 90

Code

: PFWO15, 491-030; PFWO35, 491-031; PFGWO68, 491-029; PFWO68, 491-036;

PFWO90, 491-033

Material uses

: Purity FG WO White Mineral Oil 15, 35, 68, 90 are highly refined white mineral oils intended

for the food processing industry.

NSF 3H and H1 Registered.

This product complies with FDA 21 CFR 172.878 "White Mineral Oil" and 21 CFR

178.3620(a) regulations for direct food contact."

Manufacturer

PETRO-CANADA P.O. Box 2844

150 - 6th Avenue South-West

Calgary, Alberta

T2P 3E3

In case of emergency

Petro-Canada: 403-296-3000 **Canutec Transportation:**

613-996-6666

Poison Control Centre: Consult local telephone directory for emergency number(s).

2 . **Hazards identification**

Physical state

: Viscous liquid.

Odour

Mild petroleum oil like.

OSHA/HCS status

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and

available for employees and other users of this product.

Emergency overview

: No specific hazard.

Routes of entry

Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eyes

Slightly irritating to the eyes.

Skin

: Slightly irritating to the skin.

Inhalation

No known significant effects or critical hazards.

Ingestion

No known significant effects or critical hazards.

Medical conditions

aggravated by over-

exposure

Repeated skin exposure can produce local skin destruction or dermatitis. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin

irritation.

See toxicological information (section 11)

Composition/information on ingredients 3

CAS number <u>%</u> Name 8042-47-5 White mineral oil 100

First-aid measures

Eye contact

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Get medical attention if irritation occurs. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Continued on Next Page

Internet: lubricants.petro-canada.ca/msds

Page: 1/6

PURITY™ FG WO WHITE MINERAL OIL 15, 35, 68, 90

First-aid measures 4.

Ingestion

: Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.

Page Number: 2

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training.

5 Fire-fighting measures

Flammability of the product

: May be combustible at high temperature.

Products of combustion

Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete

combustion.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

None known.

Special exposure hazards

: No specific hazard.

Special protective

equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire hazards

: Low fire hazard. This material must be heated before ignition will occur.

Special remarks on explosion hazards

: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

6. Accidental release measures

Personal precautions

: Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment.

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up

: If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dyke spilt material or otherwise contain it to ensure runoff does not reach a waterway. Place spilt material in an appropriate container for disposal.

Handling and storage

Handling

: Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk. Evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/vapour/spray. Wear suitable protective clothing. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles.

Storage

Keep container tightly closed. Store away from incompatible materials (see section 10). Keep container in a cool, well-ventilated area.

Exposure controls/personal protection

Product name

Exposure limits

White mineral oil

ACGIH TLV (United States). Notes: (oil mist) TWA: 5 mg/m³ 8 hour(s).

STEL: 10 mg/m³ 15 minute(s).

Consult local authorities for acceptable exposure limits.

Engineering measures

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protection

Continued on Next Page

Internet: lubricants.petro-canada.ca/msds

Page: 2/6

PURITY™ FG WO WHITE MINERAL OIL 15, 35, 68, 90

Page Number: 3

Exposure controls/personal protection 8.

Eyes

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour filter

Hands

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommended: neoprene, nitrile, polyvinyl alcohol (PVA), Viton.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Physical and chemical properties 9

Physical state : Viscous liquid.

Flash point Open cup: \geq 175°C (347°F) [Cleveland.]

Auto-ignition temperature

Not available. Flammable limits : Not available. Colour Clear and bright. Mild petroleum oil like. **Odour**

Not available. pН **Boiling/condensation point** : Not available.

Pour Point : **15**: -18°C (0°F), **35**: -18°C (0°F), **68**: -18°C (0°F), **90**: -15°C (5°F)

Melting/freezing point : Not available.

0.859 to 0.870 kg/L @ 15°C (59°F) Relative density

Not available. Vapour pressure Vapour density Not available. Not available. Volatility **Odour threshold** : Not available. **Evaporation rate** : Not available.

: **15**: 15.00 cSt @ 40°C (104°F), 3.43 cSt @ 100°C (212°F); **35**: 36.06 cSt @ 40°C **Viscosity**

(104°F), 5.82 cSt @ 100°C (212°F); 68: 67.77 cSt @ 40°C (104°F), 8.86 cSt @ 100°C

(212°F); 90: 103 cSt @ 40°C (104°F), 11.8 cSt @ 100°C (212°F)

Solubility : Insoluble in water. Not available. LogK_{ow} Physical/chemical : Not available.

10 . Stability and reactivity

Stability and reactivity

properties comments

: The product is stable.

Conditions of instability

: Not available.

Incompatibility with various

substances

products

: Reactive with oxidizing agents.

Hazardous decomposition

: May release COx, smoke and irritating vapours when heated to decomposition.

Continued on Next Page

Internet: lubricants.petro-canada.ca/msds

Page: 3/6

PURITY™ FG WO WHITE MINERAL OIL 15, 35, 68, 90

Page Number: 4

10. Stability and reactivity

Hazardous polymerisation : Will not occur.

11. Toxicological information

Toxicity data

Product/ingredient name Result **Route Species** Test White mineral oil LD50 >5000 mg/kg Oral Rat LD50 >2000 mg/kg Rabbit Dermal >2500 mg/m³ (4 LC50 Inhalation Rat

hours)

Specific effects

Carcinogenic effects
 Mutagenic effects
 No known significant effects or critical hazards.
 Teratogenicity /
 No known significant effects or critical hazards.

Sensitisation

Reproductive toxicity

Ingestion : No known significant effects or critical hazards.Inhalation : No known significant effects or critical hazards.

Eyes : Slightly irritating to the eyes.

Skin : Slightly irritating to the skin.

Synergistic products : Not available.

12. Ecological information

Ecotoxicity data

Product/ingredient name Species Period Result

Environmental precautions

products of biodegradation

: No known significant effects or critical hazards.

Bioconcentration factor

BOD and COD

Biodegradable/OECD

Mobility

Not available.

Not available.

Not available.

Not available.

Not available.

13. Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Waste disposal

: The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Continued on Next Page

Internet: lubricants.petro-canada.ca/msds

Page: 4/6

14. Transport information

Regulatory information	UN number	Proper shipping name	Class	PG*	Label	Additional information
TDG Classification	Not regulated.	-	-	-		-
DOT Classification	Not available.		Not available.	-		-

PG* : Packing group

15. Regulatory information

United States

HCS Classification: Not regulated.

Canada

WHMIS (Canada) : Not controlled under WHMIS (Canada).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

EU regulations

Risk phrases : This product is not classified according to EU legislation.

International regulations

International lists

AUSTRALIAN INVENTORY (AICS) : Listed **Canada inventory status** : Listed **CHINA INVENTORY (IECS)** : Listed **EC INVENTORY (EINECS/ELINCS)** : Listed **JAPAN INVENTORY (ENCS)** : Listed **KOREA INVENTORY (ECL)** : Listed **PHILIPPINE INVENTORY (PICCS)** : Listed TSCA 8(b) inventory : Listed

16. Other information

Hazardous Material Information System (U.S.A.)

Health 1
Fire hazard 1
Reactivity 1
Personal protection B

National Fire Protection Association (U.S.A.)

Health 1 0 Instability
Special

References: Available upon request.

TM/MC Marque de commerce de Petro-Canada - Trademark

Date of printing : 4/1/2009.

Date of issue : 4/1/2009.

Date of previous issue : 9/24/2008.

Responsible name : Product Safety - JDW

Version : 9

Page Number: 6

16. Other information

For Copy of (M)SDS

: The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:

Internet: lubricants.petro-canada.ca/msds

Lubricants:

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285

For Product Safety Information: (905) 804-4752

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.