



Performance 500 Automatic Transmission Fluid (ATF) MD-3

CUSTOMER BENEFITS

- Protection
- Outstanding thermal and oxidative stability
- Chatter suppression
- Low foaming and easy pumping

FEATURES

Performance 500 Automatic Transmission Fluid is a passenger car and light truck automatic transmission fluid intended for most automatic transmissions requiring a high performance, multi-purpose, power transmission fluid. Performance 500 ATF is formulated to maintain friction control and smooth shift action under the most extreme operating conditions. Our additive package prevents the formation of lacquers, sludge, or other harmful deposits. Manufactured with pristine base oils contribute to withstanding oxidation, increased thermal stability, friction control, load-carrying ability, corrosion and wear protection. Performance 500 Automatic Transmission Fluid provides outstanding durability under the most severe operating condition:

- maintains friction control for smooth shift action
- is specially formulated to prevent shudder.
- retains low temperature fluidity and high temperature stability for long operating periods.
- protects automatic transmission fluid coolers from corrosion.
- recommended for use where *Ford MERCON® or **General Motors DEXRON®-III fluids are specified
- also can be utilized as a power steering fluid.

*MERCON is a registered trademark of the Ford Motor Corporation **DEXRON is a registered trademark of the Ford Motor Corporation

APPLICATIONS

Performance 500 Automatic Transmission Fluid is designed for use in most pre-2006 automatic transmissions built by General Motors, Ford Motor Company and other makes requiring a high-performance, multi-purpose, power transmission fluid. Performance 500 automatic Transmission Fluid is also used as light oil in compressors, pumps and hydraulic systems.

Always check your owner's manual to determine the proper automatic transmission fluid for your transmission.

TYPICAL TEST DATA

Test	ASTM	Unit	Results
Viscosity @ 100 °C	D445	cSt	7.0
Viscosity @ 40 °C	D445	cSt	36.5
Pour Point (max)	D5949	°C	-51
Zinc	D4951	ppm	1
Calcium	D4951	%wt.	0.030
Flash Point (min)	D92	°C	201
Color	-	-	Red
API Gravity	-	-	32.5

Note: Typical test data are averages only, minor variations which do not affect the products ability to perform are to be expected.

*Conforms, meets, and in many cases exceeds industry standards.

Information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA, THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. SC Fuels assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of SC Fuels.