



## Performance 500 PUMP OIL 150

### PRODUCT DESCRIPTION

Performance 500 Pump Oil 150 is a custom blended highly refined base fluids with additives to produce a premium, extended life, rust and oxidation-inhibited lubricant. They are formulated to give good demulsibility and antifoam properties. Performance 500 Pump Oil 150 also has excellent lubricity and anti-wear characteristics.

### APPLICATIONS

Performance 500 Pump Oil 150 is a premium lubricant formulated for oil circulating systems such as rotary screw air compressors and hydraulic applications requiring anti-wear. The conventional mineral oils are commonly used in rotary screw air compressors.

### TYPICAL TEST DATA

Test	ASTM	Unit	Typical
API Base Oil Category	APT 1509 E.1.3		Group II
Appearance			Bright & Clear
Odor			None
Viscosity @ 40 C	D445	cSt	40
Viscosity @ 100 C	D445	cSt	7.1
Viscosity Index	-	-	105
Pour point	D5950	°C	-15
Flash Point	D92	°F	390
Total Sulfur, wt. %	D3120	Wt%	0.02
Saturates, wt. %	D2887	Wt%	92
Total Ash Content	D482	Wt %	<0.001
API Gravity	D287	-	34.4
Lbs/Gallon			7.1
Total Acid Number	D664	mgKOH/g	< 0.01
Color	D1500		1

Note: Typical test data are averages only, minor variations which do not affect the products ability to perform are to be expected. \*Conforms, meets, and in many cases exceeds industry standards.

Information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA, THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. SC Fuels assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of SC Fuels.