



Performance 500 SynGear Synthetic High Performance Multi-Purpose Gear Lubricant

Product Description

Performance 500 SYNGEAR is a synthetic multi-purpose gear lubricant designed specifically for high performance automotive applications. Required for many European automobile modes, this lubricant is well suited for areas where low temperature start-ups may be encountered.

Features

- Allows start up at extremely low temperature
- EP additives for wear protection
- Good rust protection
- Improves fuel economy
- Very high VI for wide temperature operation
- Non-corrosive and foam resistant

Typical Uses:

- API Service GL-4 & GL-5
- Meets SAE J2360 requirements
- High performance European automobiles
- MACK Specifications GO-G, GO-H and GO-J

Typical Specifications:

GRADE, SAE	75W-90	75W-140
Gravity, °API	29.1	28.6
Flash Point, °F	420	420
Viscosity:		
cSt @ 40 °C	96	163
cSt @ 100 °C	14.7	26.5
SUS @ 100 °F	490	760
SUS @ 210 °F	78.2	126
Brookfield VISC - 40°C, CPS	80,000	90,000
Phosphorus, Wt %	0.099	0.099
Viscosity Index	158	199
Color, D-1500	2.5	2.0

***Contains High Performance Additive Chemistry.
Values shown here are typical and may vary***