

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/19/2018

Revision date: 07/24/2018

Supersedes: 11/19/2018

Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : SPX TRACTOR HYDRAULIC FLUID
Synonyms : SPX UNIVERSAL TRACTOR HYDRAULIC

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Lubricants and additives

1.3. Supplier

Manufacturer

General Petroleum Corporation, DBA Maxum Petroleum

19501 South Santa Fe Avenue

Rancho Dominguez, CA 90221

United States of America

T: (310) 356-2757

email: customer.service@maxumpetroleum.com

website: <http://www.generalpetroleum.com>

1.4. Emergency telephone number

Emergency number : (800) 424-9300 CHEMTREC (24 HOURS)
Transportation: (310) 356-2757

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Eye Dam. 1	H318	Causes serious eye damage
Repr. 2	H361	Suspected of damaging fertility or the unborn child
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways

Full text of hazard classes and H-statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H304 - May be fatal if swallowed and enters airways
H318 - Causes serious eye damage
H361 - Suspected of damaging fertility or the unborn child

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear eye protection, protective gloves.
P301+P310 - If swallowed: Immediately call a poison center or doctor
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention.
P331 - Do NOT induce vomiting.

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%)	(CAS-No.) 64742-54-7	40 - 50	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%)	(CAS-No.) 64742-55-8	40 - 50	Asp. Tox. 1, H304
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	(CAS-No.) 4259-15-8	4.0 - 7.5	Eye Dam. 1, H318 Aquatic Chronic 2, H411
2,6-di-tert-butylphenol	(CAS-No.) 128-39-2	1 - 3.75	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Mineral oil	(CAS-No.) mixture	1 - 3	Asp. Tox. 1, H304
Triphenyl phosphite	(CAS-No.) 101-02-0	0.25 - 0.75	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2-ethylhexan-1-ol	(CAS-No.) 104-76-7	0.1 - 0.75	Flam. Liq. 4, H227 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
O,O,O-triphenyl phosphorothioate	(CAS-No.) 597-82-0	0.1 - 0.45	Repr. 2, H361 Aquatic Chronic 4, H413

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical attention.
- First-aid measures after skin contact : Wash skin with mild soap and water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Never give anything by mouth to an unconscious person. To prevent aspiration, keep head below knees. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into lungs. Immediately call a poison center or doctor/physician.

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : May damage fertility. May damage the unborn child. May cause serious damage to eyes. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

Reactivity : Reacts with : Strong acids. Oxidizer.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Stop leak, if possible without risk. Eliminate ignition sources. Ventilate spillage area. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Stop leak, if possible without risk. Eliminate every possible source of ignition. Ventilate area. Avoid contact with skin and eyes.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Product can accumulate electrostatic charges that may cause fire by electrical discharges. Never use pressure to empty container. Over pressure may rupture containers, cause serious injury, cause or accelerate fire.

Precautions for safe handling : Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Take precautionary measures against static discharge. Store in a well-ventilated place. Keep container tightly closed.
- Incompatible materials : Strong oxidizers. Strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³

zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)		
Not applicable		

2,6-di-tert-butylphenol (128-39-2)		
Not applicable		

Mineral oil (mixture)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³

Triphenyl phosphite (101-02-0)		
Not applicable		

2-ethylhexan-1-ol (104-76-7)		
Not applicable		

O,O,O-triphenyl phosphorothioate (597-82-0)		
Not applicable		

Monitoring methods		
Monitoring methods (oil)	NIOSH Manual of Analytical Methods, Mixed Cellulose Ester Filter (MCEF) 0.8 microns	

8.2. Appropriate engineering controls

- Appropriate engineering controls : Avoid splashing. Avoid creating mist or spray. Either local exhaust or general room ventilation is usually required.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. VITON gloves. nitrile rubber gloves

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection:

Use splash goggles when eye contact due to splashing is possible

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Use an approved respirator equipped with oil/mist cartridges.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Mobile liquid.
Color	: Blue/ amber/ red/ orange
Odor	: petroleum-like odor
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: <= 315 °C
Flash point	: 215 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: < 0.01 mm Hg @ 37.8 °C (100 °F)
Relative vapor density at 20 °C	: > 1
Relative density	: 0.89 @ 15.6 °C (60.1°F)
Solubility	: Soluble in : Organic solvents. insoluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 11.7 mm ² /s @ 100 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with : Strong acids. Oxidizer.

10.2. Chemical stability

Stable under normal conditions.

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Do not store with incompatible materials.

10.5. Incompatible materials

Strong acids. Strong oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.53 mg/l/4h

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg body weight
LC50 inhalation rat (mg/l)	> 10.5 mg/l/4h

zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)

LD50 oral rat	3100 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
ATE US (oral)	3100 mg/kg body weight

2-ethylhexan-1-ol (104-76-7)

LD50 oral rat	2047 mg/kg male
LD50 dermal rat	> 3000 mg/kg
LC50 inhalation rat (mg/l)	0.89 mg/L (vapour); 5.3 mg/L (vapour (1.1 mg/L) aerosol (4.3 mg/L))
ATE US (oral)	2047 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

O,O,O-triphenyl phosphorothioate (597-82-0)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: 11.7 mm ² /s @ 100 °C

Likely routes of exposure	: Dermal.
Potential Adverse human health effects and symptoms	: May damage fertility. May damage the unborn child. May cause serious damage to eyes. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Risk of lung edema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

EC50 Daphnia 1	> 10000 mg/l
----------------	--------------

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

LC50 fish 1	101 mg/l > 100 mg/l LL50. 101 is put in for calculations, per request of IPAC
-------------	---

zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)

LC50 fish 1	46 mg/l
-------------	---------

2-ethylhexan-1-ol (104-76-7)

LC50 fish 1	17.1 mg/l 96 h
-------------	----------------

NOEC (acute)	14 mg/l 96 h
--------------	--------------

12.2. Persistence and degradability

SPX TRACTOR HYDRAULIC FLUID

Persistence and degradability	This product is not expected to be biodegradable.
-------------------------------	---

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

2-ethylhexan-1-ol (104-76-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

2-ethylhexan-1-ol (104-76-7)

Log Pow	2.9
---------	-----

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Waste disposal recommendations : If recycling is not possible, eliminate in accordance with local valid waste disposal regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT
Not regulated.

Transportation of Dangerous Goods

Not regulated.

Transport by sea

- Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-di-tert-butylphenol), 9, III, MARINE POLLUTANT
- UN-No. (IMDG) : 3082
- Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
- Class (IMDG) : 9 - Miscellaneous dangerous substances and articles
- Packing group (IMDG) : III - substances presenting low danger

Air transport

- Transport document description (IATA) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-di-tert-butylphenol), 9, III
- UN-No. (IATA) : 3082
- Proper Shipping Name (IATA) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
- Class (IATA) : 9 - Miscellaneous Dangerous Goods
- Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2,6-di-tert-butylphenol (128-39-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

Mineral oil (mixture)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Triphenyl phosphite (101-02-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-ethylhexan-1-ol (104-76-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

O,O,O-triphenyl phosphorothioate (597-82-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on the Canadian DSL (Domestic Substances List)

2,6-di-tert-butylphenol (128-39-2)

Listed on the Canadian DSL (Domestic Substances List)

Mineral oil (mixture)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

Triphenyl phosphite (101-02-0)

Listed on the Canadian DSL (Domestic Substances List)

2-ethylhexan-1-ol (104-76-7)

Listed on the Canadian DSL (Domestic Substances List)

O,O,O-triphenyl phosphorothioate (597-82-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

2,6-di-tert-butylphenol (128-39-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Triphenyl phosphite (101-02-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

2-ethylhexan-1-ol (104-76-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

O,O,O-triphenyl phosphorothioate (597-82-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on Taiwan National Chemical Inventory
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Triphenyl phosphite (101-02-0)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Chinese Catalog of Hazardous Chemicals.
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on Taiwan National Chemical Inventory
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the AICS (Australian Inventory of Chemical Substances)

2-ethylhexan-1-ol (104-76-7)

Listed on KECI (Korean Existing Chemicals Inventory)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on Taiwan National Chemical Inventory
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 07/24/2018
Data sources : European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
European Chemicals Agency (ECHA) Registered Substances list. Accessed at <http://echa.europa.eu/>.
Component Supplier SDSs.
Manufacturer Information.

Full text of H-phrases:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4
Asp. Tox. 1	Aspiration hazard Category 1

SPX TRACTOR HYDRAULIC FLUID

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Abbreviations and acronyms:

ACGIH (American Conference of Government Industrial Hygienists)
ATE: Acute Toxicity Estimate
CAS (Chemical Abstracts Service) number
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
IARC: International Agency for Research on Cancer
LD50: Lethal Dose for 50% of the test population
STEL: Short Term Exposure Limits
TWA: Time Weighted Average

- NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
- NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



SDS US (GHS HazCom 2012)

SDS prepared by:
The Redstone Group, LLC
6077 Frantz Rd. Suite 206
Dublin, OH USA 43017
T 614-923-7472
www.redstonegrp.com.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product