



SPX FORMULA

Low Ash Natural Gas Engine Oil

SAE 30W, 40W, 15W-40

BENEFITS

- Excellent anti-wear protection and extreme soot control
- Enhanced oxidation control & withstand thermal breakdown
- Low oil consumption
- Cleaner engine, maximum performance and less maintenance
- Low phosphorus formulation

FEATURES

The latest additive technology blended with premium Group II base oils to produce the highest quality low ash natural gas engine oil. SPX NGENO is formulated for all stationary natural gas engines including Waukesha and CATERPILLAR 3600, 3500 series engines in both low and high sulfur operating environments.

TYPICAL TEST DATA

Test	ASTM	Unit	SAE 30W	SAE 40W	SAE 15w-40
Viscosity, Cold Crank	D5293	C/Poise	-	-	6448
Viscosity @ 40 C	D445	cSt	85.0	120	115.6
Viscosity @ 100 C	D445	cSt	11.5	13.0	14.33
Viscosity Index	-	-	120	115	130
Pour point	D97	C	-30	-24	-35
Flash Point	D92	C	210	220	220
Base Number	D2896	mgKOH/g	5.6	5.6	5.6
Zinc Wt%	-	Wt%	0.30	0.30	0.30
Sulfated Ash	D874	Wt%	0.5	0.5	0.05
API Gravity	D287	-	30.5	28.0	29.1

Note: Typical test data are averages only, minor variations which do not affect the products ability to perform are to be expected.

*Conforms, meets, and in many cases exceeds industry standards.

Information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA, THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Maxum assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Maxum.

MAXUM PETROLEUM 19501 S. SANTA FE AVE, RANCHO DOMINGUEZ, CA 90221