



# **SPX Tractor Hydraulic Fluid (THF)**

### **CUSTOMER BENEFITS**

- Superior gear performance
- Anti-wear protection
- Outstanding thermal and oxidative stability
- Prevents rust and corrosion
- Chatter suppression

#### **FEATURES**

SPX THF is a multifunctional type fluid formulated to advance the life of your tractor. Our unique formulation uses pristine base stocks blended with a top tier friction modifying additive pack, a high viscosity index improver, and the finest pour point suppressant available. This special blend produces the highest quality Tractor Hydraulic Fluid. Under extreme conditions both humid and in the presence of high temperatures, SPX THF provides maximum protection by withstanding thermal breakdown and remaining hydrolytically stable.

Suitable\* for use in tractors where the following specifications are noted:

- John Deere JDM, J20C, and J20D (back serviceable to John Deere JDM J20A and J20B)
- Massey Ferguson CMS1135, CMS1141, CMS1143, CMS 1145
- **CNH** MAT3525 (Ford ESN-M2C-134-D, FNHA-2-C-201.00)
- Ford ESN- M2C86-B and M2C86-C
- CASE MS-1210
- CNH MAT3509 (Case MS 1230)
- Allison C-4
- Kubota UDT

## **APPLICATIONS**

SPX THF is recommended for use wherever there is a high demand for quality and performance. It is designed as a multifunctional and multi-seasonal fluid for use in all types of tractors and construction equipment.

#### TYPICAL TEST DATA

Test	ASTM	Unit	Results
Viscosity @100 °C	D445	cSt	9.0
Viscosity @ 40 °C	D445	cSt	50.0
Viscosity Index (min)	-	-	162
Pour Point (max)	D5949	°C	-40
Phosphorus	D4951	%wt.	0.100
Flash Point (min)	D92	°C	225
Color	-	-	Orange
API Gravity	-	-	31.5

